



	PART DESCRIPTION	MATERIAL
①	SM1RR	ANODIZED ALUMINUM
②	AD254-45-B	N-LAK22/N-SF6HT
③	SM1L12-A	ANODIZED ALUMINUM



NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTHS: 706.5 nm, 855 nm, AND 1015 nm
- FOCAL LENGTH: 45.0mm $\pm 1\%$
- BACK FOCAL LENGTH (REF): 39.6mm
- LENS DIAMETER: 25.4mm $+0.00/-0.10\text{mm}$
- LENS CENTER THICKNESS: 9.4mm
- CLEAR APERTURE: $>90\%$ OF LENS DIAMETER
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: <3 arcmin
- COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 650-1050nm
0° AOI, ON BOTH OPTICAL SURFACES

FOR INFORMATION ONLY NOT FOR
MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	睿创光科 Mounted D25.4mm, F=45mm, Near IR Achromat, B Coated			
DRAWN	CWD	2022/5/18	AD254-45-B-ML			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A		2:1	A