



NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 588nm
- FOCAL LENGTH: $f=-25.0.0\text{mm} \pm 1\%$
- BACK FOCAL LENGTH(REF): $bf=-26.0\text{mm}$
- CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: $\leq 3\text{arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
- THICKNESS TOLERANCE: $\pm 0.1\text{mm}$

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

| | | | | | | |
|---|------|---|---|---|-------|-----|
| DRAWING PROJECTION | |  | |  | | |
| | NAME | DATE | D25.4 F=-25.0 UV Fused Silica Bi Concave Lens | | | |
| DRAWN | CWD | 2022/5/18 | EC4254--25-1 | | | |
| APPROVAL | ZSB | 2022/5/18 | MATERIAL | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES | | | UV GRADE FUSED SILICA | 0.04kg | 1:1 | A |