


NOTES/SPECIFICATIONS.

- 1. DESIGN WAVELENGTH: 587.6nm
- 2. FOCAL LENGTH: 50.0mm±1%
- 3. BACK FOCAL LENGTH (REF): 46.4mm
- 4. CLEAR APERTURE: ≥90% OF DIAMETER
- 5. SURFACE QUALITY: 10-5 SCRATCH-DIG
- 6. CENTRATION: <3arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1mm
- 8. THICKNESS TOLERANCE: ± 0.1 mm
- 9. DIFFRACTION LIMITED DIAMETER @632.8nm. 5.0mm
- 10. DIFFRACTION LIMITED DIAMETER @1064nm: 6.0mm
- 11. COATING.BBAR Ravg<0.5% FROM 1050-1700nm,0° AOI, ON OUTER OPTICAL SURFACES



DRAWING PROJECTION			PEOPTICS			
	NAME	DATE	D25.4, F=50.0, N-BK7, C Coated, Best Form Lens			
DRAWN	C₩D	2022/5/18	BFBX1254-50-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-BK7	0.0061kg	2:1	A