



- NOTES/SPECIFICATIONS:
  1. DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: f=19.9mm ± 1%

  BACK FOCAL LENGTH(REF): bf=19.0mm

  CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: <3arcmin
- DIAMETER TOLERANCE: +0.0/-0.1mm THICKNESS TOLERANCE: ±0.1mm
- COATING: BBAR Ravg<0.5% FROM 350nm-700nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM  $\frac{[in]}{mm}$ THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

| DRAWING<br>PROJECTION                              |      |           | 不容创光科<br>RCOPTICS                         |        |       |     |
|--|------|-----------|---|--------|-------|-----|
|  | NAME | DATE      | D9.0 F=20.0 N-BK7 A Coated Bi Convex Lens |        |       |     |
| DRAWN  | CWD  | 2022/5/18 | BX1009-20-A                               |        |       |     |
| APPROVAL   | ZSB  | 2022/5/18 | MATERIAL                                  | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES |      |           | N-BK7                                     |        | 6:1   | A   |