





SECTION A-A

NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6 nm
- FOCAL LENGTH: $f=1003.5 \text{ mm} \pm 1\%$
- BACK FOCAL LENGTH(REF): $bf=1002.3 \text{ mm}$
- CLEAR APERTURE: $> \varnothing 45.72 \text{ mm}$
- SURFACE QUALITY: 20-10 SCRATCH-DIG
- CENTRATION: $\leq 3 \text{ arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1 \text{ mm}$
- THICKNESS TOLERANCE: $\pm 0.1 \text{ mm}$
- SURFACE IRREGULARITY: $\leq \lambda/4$, @633 nm
- SPHERICAL SURFACE POWER: $\leq 3\lambda/2$, @633 nm
- COATING(S1,S2): VAR R<0.25% PER SURFACE FOR 532 nm, 0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 			
	NAME	DATE	F=1000.0mm, D50.8UVFS Bi-Convex Lens, 532nm coating			
DRAWN	CWD	2022/5/18	EX4508-1000-532			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.0149kg	1:1	A