


#### NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6 nm
- FOCAL LENGTH:  $f=1003.5 \text{ mm} \pm 1\%$
- BACK FOCAL LENGTH(REF):  $bf=1002.3 \text{ mm}$
- CLEAR APERTURE:  $> \varnothing 45.72 \text{ mm}$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION:  $\leq 3 \text{ arcmin}$
- DIAMETER TOLERANCE:  $+0.0/-0.1 \text{ mm}$
- THICKNESS TOLERANCE:  $\pm 0.1 \text{ mm}$
- COATING(S1,S2): BBAR  $R_{avg} < 0.5\%$  FROM 350-700 nm,  $0^\circ$  AOI

FOR INFORMATION ONLY  
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	F= 1000.0 mm, D50.8UV Fused Silica Bi-Convex Lens, A Coateding			
DRAWN	CWD	2022/5/18	EX4508-1000-A			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.01493kg	1:1	A