

|   | ITEM                            | MATERIAL         |  |  |
|---|---------------------------------|------------------|--|--|
| 1 | BLACK ANODIZED<br>MOUNTING RING | 6061-T6 ALUMINUM |  |  |
| 2 | ROUND<br>CYLINDRICAL LENS       | N-BK7            |  |  |





## NOTES/SPECIFICATIONS:

- FOCAL LENGTH: -75.0mm ±1%
- WORKING DISTANCE: -71.8mm
- DESIGN WAVELENGTH: 587.6nm
- CLEAR APERTURE: >21.0mm SURFACE QUALITY: 60-40 SCRATCH-DIG
- CENTRATION: ≤ 3 arcmin
  COATING: BBAR 650-1050nm, Ravg < 0.5%, 0° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

| DRAWING<br>PROJECTION                              |      |           | 客创光科<br>RCOPTICS   |            |       |     |  |
|--|------|-----------|--|------------|-------|-----|--|
|  | NAME | DATE      | D25.4 F=-75 Mounted Rd N-BK7 B Coated Plano Concave Cyl Lens |            |       |     |  |
| DRAWN  | CWD  | 2022/5/18 | PCY1254RM75-B  |            |       |     |  |
| APPROVAL   | ZSB  | 2022/5/18 | MATERIAL   | WEIGHT     | SCALE | REV |  |
| FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES |      |           | SEE TABLE  | 0. 00396kg |       | С   |  |