

	ITEM	MATERIAL				
1	BLACK ANODIZED MOUNTING RING	6061-T6 ALUMINUM				
2	ROUND CYLINDRICAL LENS	UV FUSED SILICA				





## NOTES/SPECIFICATIONS:

- FOCAL LENGTH: -50.0mm ±1% WORKING DISTANCE: -44.9mm DESIGN WAVELENGTH: 587.6nm CLEAR APERTURE: >21.0mm SURFACE QUALITY: 40-20 SCRATCH-DIG
- 1. 2. 3. 4. 5. 6. 7. CENTRATION: ≤ 3arcmin COATING: BBAR 1050-1700nm, Ravg < 0.5%, 0° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			客创光科 RCOPTICS				
	NAME	DATE	D25.4 F= -50 Mounted Rd UVFS C Coated Plano-Concave Cyl Lens				
DRAWN	CWD	2022/5/18	PCY4254RM50-C				
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES		SEE TABLE	0. 004kg		A		